

Pipe Fittings

Specification:




Butt Weld, ASTM A234/SA234, A420/SA420

Grades:

WPB, WPL6

NOTE:

Full Range of 15lb BSP Fitting Available

Wall Thickness 1/2" to 16" NB Sch 20s - Sch 160s,XXS		90° Elbow 	45° Elbow 	N.B. Pipe Size Run & Outlet	Reducing Tees 	
NB ins. mm	O.D. ins. mm	A ins. mm	B ins. mm	ins. mm	C ins. mm	D ins. mm
1/2	21.3	38.1	15.9	1 X 1/2 28.4 X 12.7	38	38
3/4	26.7	38.1	11.1	1 X 3/4 25.4 X 19.05	38	38
1	33.4	38.1	22.2	1 1/2 X 1 38.1 X 25.4	57	57
1 1/4	42.2	47.8	25.4	2 X 1 1/4 50.8 X 31.75	64	51
1 1/2	48.3	57.2	28.6	2 X 1 1/2 50.8 X 38.1	64	60
2	60.3	76.2	34.9	3 X 1 1/2 76.2 X 50 X 50.8	86	73
2 1/2	73.0	95.3	44.5	3 X 2 76.2 X 50.8	86	76
3	88.9	114.3	50.8	4 X 2 101.6 X 50.8	105	89
3 1/2	101.6	133.4	57.2	4 X 3 101.6 X 76.2	105	98
4	114.3	152.4	63.5	6 X 3 152.4 X 76.2	143	124
5	141.3	190.5	79.4	6 X 4 152.4 X 101.6	143	130
6	168.3	228.6	95.3	8 X 6 203.2 X 152.4	178	168
8	219.1	304.8	127.0			
10	273.0	381.0	158.8			
12	323.9	457.2	190.5			
14	355.6	533.4	222.3			
16	406.4	609.6	254.0			

Wall Thickness
1/2" to 16" NB
Sch 20s - Sch 160s,XXS


Concentric Reducer




Eccentric Reducer




Equal Tee



Stub End



End Cap



NB ins.	O.D. ins. mm	E ins. mm	F ins. mm	G ins. mm	H ins. mm	I ins. mm
1/2	21.3	50.8	25.4	50.8	76.2	25.4
3/4	26.7	50.8	28.6	50.8	76.2	25.4
1	33.4	50.8	38.1	50.8	101.6	38.1
1 ¼	42.2	50.8	47.6	50.8	101.6	38.1
1 ½	48.3	63.5	57.2	50.8	101.6	38.1
2	60.3	76.2	63.5	63.5	152.4	38.1
2 ½	73.0	88.9	76.2	63.5	152.4	38.1
3	88.9	88.9	85.7	63.5	152.4	50.8
3 ½	101.6	101.6	95.3	76.2	152.4	63.5
4	114.3	101.6	104.8	76.2	152.4	63.5
5	141.3	127.0	123.8	76.2	203.2	76.2
6	168.3	139.7	142.9	88.9	203.2	88.9
8	219.1	152.4	177.8	101.6	203.2	101.6
10	273.0	177.8	215.9	127.0	254.0	127.0
12	323.9	203.2	254.0	152.4	254.0	152.4
14	355.6	-	279.4	152.4	304.8	165.1
16	406.4	-	304.8	152.4	304.8	177.8

Full Range of Hygienic Fittings to Bs 4825