

## Pipe Fittings

### Specification:

Butt Weld, ASTM A403, WPW, WPS



### Grades:

304, 304L, 316, 316L, 321


### NOTE:

Full Range of 15lb BSP Fitting Available Ex - stock

Wall Thickness  
1/2" to 16" NB  
Sch 5s, Sch 10s  
Sch 40s, Sch 80s



N.B. Pipe Size  
Run & Outlet



NB ins. mm	O.D. ins. mm	A ins. mm	B ins. mm	ins. mm	C ins. mm	D ins. mm
1/2	21.3	38.1	15.9	1 X 1/2 28.4 X 12.7	38	38
3/4	26.7	28.6	11.1	1 X 3/4 25.4 X 19.05	38	38
1	33.4	38.1	22.2	1 1/2 X 1 38.1 X 25.4	57	57
1 1/4	42.2	47.6	25.4	2 X 1 1/4 50.8 X 31.75	64	51
1 1/2	48.3	57.2	28.6	2 X 1 1/2 50.8 X 38.1	64	60
2	60.3	76.2	34.9	3 X 1 1/2 76.2 X 50 X 50.8	86	73
2 1/2	73.0	95.3	44.5	3 X 2 76.2 X 50.8	86	76
3	88.9	114.3	50.8	4 X 2 101.6 X 50.8	105	89
3 1/2	101.6	133.4	57.2	4 X 3 101.6 X 76.2	105	98
4	114.3	152.4	63.5			
5	141.3	190.5	79.4			
6	168.3	228.6	95.3			
8	219.1	304.8	127.0			
10	273.0	381.0	158.8			
12	323.9	457.2	190.5			
14	355.6	533.4	222.3			